

Minac® 12/18 Twin



Mobile, flexible and easy-to-use. The Minac brings the benefits of induction to tough-to-access workpieces

Minac increases throughput.

Fast, easy, accurate and repeatable heat delivery improves productivity.

Minac improves quality.

Minac's microcontroller feature lets you pre-set temperatures and ramp-up and dwell times. Precise repeatability of heating cycles is assured.

Minac is environment friendly.

No flames, no gas and virtually no radiant heat mean a more comfortable, more productive working environment. Good news for the natural environment, too.

Minac lets you do more.

Minac's mobility and application versatility let you perform practically any heating task.

Minac reduces costs.

Precise heat delivery means you get things right the first time. Scrap, re-working and energy costs are minimized.



Minac® 12/18 Twin

PRODUCT FEATURES

Mobile induction

Minac is light enough to be carried in a normal car. You no longer have to transport workpieces to the induction system—often a costly and time-consuming process.

Range of coils

Minac systems can be fitted with a practically limitless range of coil designs. EFD Induction are specialists at designing, testing and delivering customized, long-life coils.

Twin power output

The 'Twin' version features two independent power output that can operate simultaneously under identical or different parameters.

Split display

The 'Twin' version features two independent control panels. Each displays data for its power output. Functionality is based on our specially designed microcontroller.

Remote control

A remote control unit lets you control heating cycles via feedback to the microcontroller. Minac is available with field buses and is compatible with Profibus-DP, Interbus, Ethernet. etc.

Robot compatible

Minac can be adapted to any robot, allowing quick, no-fuss intergration into automated production lines. The HHT can easily be mounted on a robot arm.

Maximum output power

With Minac's maximum power feature you can, for limited periods of time, operate with an output power far in excess of the continuous output power.

APPLICATIONS AREAS

Minac is ideal for a wide range of applications: brazing, shrink fitting, hardening, curing, straightening, heat treatment, etc. Minac is suitable for heating all kinds of electrical conductive materials like copper, aluminum, steel, stainless steel, brass, titanium, etc.

TECHNICAL DATA

Model	Minac 12/18 Twin
Output	
Continuous output power	2x12 kW
Max. output power	2x18 kW
Duty factor / cycle time	50%/10 min
Output power regulation range	2-100 %
Frequency range	10 - 40 kHz
HHT 240 power cable length	5 m
Supply	
Supply voltage range	3x 400-480 V ± 10%
Frequency	50/60 Hz
Nominal line current	43A (RMS)
Max. line current at 360 V	64A (RMS)
Nominal apparent power	30 kVA
Maximum apparent power	40 kVA
Recommended fuse	63 Amp
Mains cable length	5 m

Cooling

Water consumption, min.	10 l/min*
Water inlet temperature	max. 35°C
Water pressure min./max.	4/6 bar *
Cooling water quality - ph	between 7.0 and 9.0

Enclosure

Ambient operating temp.	+5°C - +50°C
Outer dimensions (WxDxH)	345x708x453 mm
Weight with HHT 240	76 kg
Enclosure protection	IP 54
Color	RAL 7035 Grey
HHT 240 outer dimension (LxOD)	128 x 76.1 mm
HHT 240 weight without handle	2,5 kg

Subject to modification

* Dependent of coil